

HALOBLINDS



INSTALLATION

**Six steps.
No tools.
No drilling.**

Click the frame together, seal the edges, drop it into the window.

haloblinds.com

Keep for future reference

AT A GLANCE

Everything you're about to do

Three steps on the floor, two to seal it, one at the window.

Nothing to screw, nothing to drill, nothing to patch up when you leave.



1 Lay out the frames



2 Take the caps off



3 Push the corners home



4 Add the brush strip



5 Add the weather strip



6 Into the window

TIME

About ten minutes per window

HALOBLINDS

TOOLS

None. Everything is in the box

WHERE

Assemble on the floor, near the window

OVERVIEW

1

ASSEMBLE

Lay out the frames



Everything happens on the floor first. Clear a space near the window, roughly the size of the finished blind.

- 1 Unpack all four rails and both sealing strips. Check nothing is missing before you begin.
- 2 Lay the rails out in a rectangle with the **inner channels facing inward**.
- 3 Make sure the internal cord runs **between** the rails, never outside them.

ORDERED WITH A MOSQUITO NET?

Then the corners go together a little differently.
Scan the code for the short video before you begin.

**TIP**

Work on carpet, a rug or a towel. The frame is aluminium and a hard floor will win.

2

ASSEMBLE

Take the corner caps off



1 Cap in place



2 Cap lifted off

Each corner is closed with a cap. They come off first, so the rails can seat fully, and go straight back on afterwards.

- 1 Lift the cap off each corner. They are a press fit — pull from the outside edge.
- 2 Keep all four together. You need every one of them again in a minute.
- 3 Underneath you will see the white corner connector.

TIP

Lever against the aluminium, never against the fabric. Set the caps somewhere they cannot roll away.

3

ASSEMBLE

Push the corners home



1 Push the rails home



2 Press each cap back on

With the caps off, the connector is exposed and the rails can push all the way in. This is what makes the joint solid.

- 1 Line a rail up with the connector and push until there is **no gap** at the joint.
- 2 Check the internal cord runs **through** the connector, not pinched between the parts.
- 3 Repeat on all four corners, then press each cap back on until it sits flush.

CHECK

Run a finger over every joint. Flush, no step, no gap. Then close the blind once to check it latches properly.

4

SEAL

Add the brush strip



The brush strip is the first of two seals. It runs along the back edge of the frame, all the way round.

- 1 Peel about **ten centimetres** of backing off one end — just enough to get started.
- 2 Press it down at a corner and work along the rail, peeling more as you go.
- 3 Trim the excess, then repeat on the other three sides.

PEELING

Peel as you go — never strip the whole length at the start. Exposed adhesive picks up dust, and it only sticks properly once.

KEEP IT LOW

Mount it as low as the frame allows, right against the back edge. Sit it too high and the weather strip has nowhere left to go. Press it into a clean 90° at every corner.

5

SEAL

Add the weather strip



Same technique, one level up. This is the seal that closes the last gap between frame and recess.

- 1 Start at a corner, directly above the brush strip.
- 2 Peel and press along each side, keeping the strip **relaxed** rather than taut.
- 3 Trim at the end, and cover all four sides without gaps.

CORNERS

Never stretch the strip across a corner. Let it sit relaxed into a clean 90° and press it home — pulled tight, it springs back and opens a gap. That is where light leaks start.

6

INSTALL

Put it in the window



Two hands, one movement. On a wide window a second pair of hands makes this easier.

- 1 Hold the frame at roughly a **70° angle** to the window.
- 2 Guide the bottom into the recess first and push it firmly down.
- 3 Push the top into position until the frame sits flush all the way round.
- 4 Open and close it once to test.

DONE

That's the whole job. No screws, no holes, nothing to fill in when you move out.

HALOBLINDS



AND THAT'S IT

Properly dark.

Any light still getting in will be at a corner. Press that corner down firmly and it's gone.

QUESTIONS?

help@haloblinds.com

haloblinds.com